



Ground Preparation Equipment

CROSS DITCHER



In many geographic regions or field situations, the removal of excess water from the field requires additional efforts. Our cross ditcher is a tool that cuts a channel in a bed or berm to allow water movement in the field across the planting beds or into a drainage ditch. We make a single row unit that can be used on berms or individual planting beds and a three row unit to cut cross ditches through three beds at a time.

Cross ditchers are powered by your tractor's hydraulic system, and are controlled by the tractor driver. The driver moves to the location in the field where you need the cross-ditch. After lowering the implement over the bed, the driver

operates the side shovels that close into the center of the bed, and cuts out a section. The operator lifts the cross ditcher and moves to the next location. As he moves the tractor to the next spot, he opens the side shovels and they feather the collected soil out into the row middles.

Part # Description

BP700	1 bed cross ditcher, offset to the side
BP740	3 bed cross ditcher

When ordering a cross ditcher, the customer must specify the exact distance off center required, or the row center between planting beds. Also provide the height and width of the planting beds to be cut. All standard cross ditchers fit a standard three-point Category II hitch. Call our sales department for weights and dimensions.

TARP LAYER FOR FUMIGATION



Our tarp layer is a special piece of equipment that is used for broadcast fumigation applications. It is used to completely cover a field with plastic to minimize dissipation of the gas from the soil. The unit lays the plastic mulch over the soil and includes a system that glues two side-by-side pieces together to create a field sized tarp.

Part # Description

PS650	10 ft tarp layer for fumigation
-------	---------------------------------

Gas knives are included. Kennco does not provide hose, fittings or other components of plumbing for fumigation systems. All standard tarp layers fit a standard three-point Category II hitch. Call our sales department for weights and dimensions.